

SISI

FALL ARREST





FALL ARREST SYSTEM

Belted harness range with permanently attached shock absorbing lanyards with adjustable shoulder, leg, waist and elasticated chest straps



CODE: HARN02221



DOUBLE LEG LANYARD WITH SCAFF HOOKS

CODE: HARN02211



DOUBLE LEG LANYARD WITH SNAP HOOKS

FOR WOMEN, THE RISK OF INJURY DOES NOT STOP WHEN THE FALL DOES.

If placed below the bust area, polyester webbing can rise aggressively up and over the bust at the end of a fall, resulting in secondary related injuries to the wearer.

That's why all our SiSi harnesses are fitted with an **ADJUSTABLE ELASTICATED CHEST STRAP** that stretches in the event of a fall, substantially reducing the pressure on the bust area. Furthermore, the chest strap can be moved up and down the shoulder straps, allowing each wearer to place it in the position that is most comfortable to them without compromising on the effectiveness of the harness.



INJURY- PREVENTING ELASTICATED CHEST STRAP

Common features on SiSi CORE+ RANGE:

- Sizing:** • One size fits all
- Standards:** • SANS 50354 | SANS 50355 | SANS 50361 | SANS 50362

MATERIALS:

- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard length: 1 700mm
- Lanyard length when shock absorber is fully elongated: 3 450mm
- Chest Strap:** • 45mm UV-resistant elastic webbing
- Buckles:** • Interlocking, corrosion-resistant steel buckles
- Hooks:** • Corrosion-resistant steel hooks
 - Scaff hooks - 50mm gate opening
 - Snap hooks - 20mm gate opening



FALL ARREST SYSTEM

Standard harness range with permanently attached shock absorbing lanyards and adjustable leg and elasticated chest straps



CODE: HARN01221



DOUBLE LEG
LANYARD WITH
SCAFF HOOKS

CODE: HARN01211



DOUBLE LEG
LANYARD WITH
SNAP HOOKS

CODE: HARN01111



SINGLE LEG
LANYARD WITH
SNAP HOOK

Common features on SiSi CORE RANGE:

- Sizing:** • One size fits all
- Standards:** • SANS 50354 | SANS 50355
SANS 50361 | SANS 50362

MATERIALS:

- Harness Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard Webbing:** • 45mm UV-resistant polyester webbing with a minimum breaking load of 2,6 tonnes
- Lanyard length: 1 700mm
 - Lanyard length when shock absorber is fully elongated: 3 450mm
- Chest Strap:** • 45mm UV-resistant elastic webbing
- Buckles:** • Interlocking, corrosion-resistant steel buckles
- Hooks:** • Corrosion-resistant steel hooks
- Scaff hooks - 50mm gate opening
 - Snap hooks - 20mm gate opening



info@sisi.co.za
Proudly manufactured
in South Africa

Accredited working at heights
training and services offered by:



fallarrest@bbfsheqservices.com

Association Memberships:

